



NOTES:

1. CONCRETE PAVING SHALL BE A MINIMUM FIVE AND ONE HALF (5 1/2) SACKS PER CUBIC YARD MIX WITH A MINIMUM FLEXURAL STRENGTH OF 3,600 P.S.I. AT 28 DAYS AND A MAXIMUM SLUMP OF 3 INCHES.
2. REINFORCING STEEL SHALL BE IN ACCORDANCE WITH THAT REQUIRED UNDER THE GENERAL PAVING NOTES FOR THE CITY OF BENBROOK.
3. EXPANSION JOINTS SHALL BE PROVIDED AT THE R.O.W. LINE OF THE FIRE LANE APPROACH AND AT A MAXIMUM OF 400 FOOT SPACINGS. TRANSVERSE SAW JOINTS SHALL BE PROVIDED AT 20' MAXIMUM SPACINGS.
4. WHERE A CURB IS USED, THE REQUIRED CLEARANCE SHALL BE MEASURED FROM THE CURB FACE TO ANY PERMANENT TRAFFIC OBSTACLE.

FEBRUARY 2018

NOT TO SCALE

REVISIONS:



City of Benbrook
 911 Winscott Road
 Benbrook, Texas 76126
 817-249-3000

FIRE LANE
 PAVING SECTION
 FD-002